



## 3625 HT VC

3625 HT VC - Compactor with VC crusher drum



- ▶ Flexible application thanks to change holder system
- ▶ For breaking up or crushing hard materials
- ▶ Crushes and compacts
- ▶ With high point load thanks to the latest chiselling technology
- ▶ Barrel bands enable safe transportation and loading
- ▶ Heavy-duty equipment



# 3625 HT VC

3625 HT VC - Compactor with VC crusher drum



## 3625 HT VC

### Weights

Operating weight with cab	kg	25420
Operating weight, max.	kg	25940
Axle load, front/rear	kg	17075/8345
Load per tyre, rear	kg	4172,5

### Machine dimensions

Max. working width	mm	2220
Lateral overhang, left/right	mm	160/160
Ground clearance, left/right	mm	490/490
Ground clearance, centre	mm	420
Turning radius, inside	mm	4590
Drum type, front		VC
Drum thickness, front	mm	35
Tool holder, quantity		150
Size of tyres, rear		EM 23.5-R25 XTLA

### Diesel engine

Manufacturer		DEUTZ
Version		TCD 2012 L06 2V
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
Emissions standard EU/USA		III A / Tier 3
Fuel tank, capacity	L	290

### Drive

Hydrostatic drive, front/rear		Wheel motor/axle
Regulation, infinitely variable		Hammtronic
Speed, infinitely variable	km/h	0 - 8,0
Climbing ability, vibration on/off	%	61/66

### Vibration

Vibration frequency, front	Hz	27
Amplitude, front	mm	2,09
Centrifugal force, front	kN	351

### Steering

Steering, type		Articulated steering
Steering, actuation		hydrostatic, steering wheel
Steering angle +/-	°	30
Oscillation angle +/-	°	10

### Equipment

Automatic frequency control with digital display, Double-sided access, Spring-mounted driver's seat, Speed pre-selection, Excellent engine power with traction control, Hammtronic – automatic traction, slip and frequency control, Tilttable GRP bonnet, Modern information and indicator display, Engine management, Swivelling steering and instrument console, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Transportation bands for VC drum, Compression meter

### Optional equipment

Spotlights, Exterior and interior mirrors, Tachograph, HCQ-GPS compaction documentation system, HCQ compaction meter, Heating with dust-free ventilation, Air conditioning, Radio, ROPS/FOPS, Sound insulation, Sun roof

<b>Total length</b>	<b>L</b>	<b>6591</b>
<b>Width</b>	<b>B</b>	<b>2540</b>
<b>Total height</b>	<b>H</b>	<b>3065</b>
<b>Wheel base</b>	<b>A</b>	<b>3186</b>
<b>Drum width</b>	<b>X</b>	<b>2220</b>
<b>Drum diameter</b>	<b>D</b>	<b>1710</b>
<b>Width over tyres</b>	<b>Y</b>	<b>2160</b>
<b>Diameter of tyres</b>	<b>R</b>	<b>1610</b>
<b>Height loading, min.</b>	<b>HI</b>	<b>2360</b>

