



75 HP

MF 375 Xtra

2WD, Simple yet powerful machinery

Key features

- High performance, fuel efficient, 4 cyl diesel engine
- Heavy-duty rear axle
- Heavy-duty front support
- Hydrostatic steering

Powerful yet economical



FROM MASSEY FERGUSON



Specifications

Engine Performance	
Engine hp power - * Certified to BS AU 141a : (1971)	@ 2200rpm 75 (B.S)*
Max torque	@ 1400rpm 290 Nm
PTO power at rated engine speed	69.5 hp**
Engine	
Engine type/no. of Cylinders/Capacity/Aspiration	Diesel 4.41 / 4 / 4.1 / Natural
Throttle control	Hand and foot
Exhaust	Vertical
Clutch	Dual
Transmission	
Type	Sliding Spur 8 forward, 2 reverse road speed 30 kph at 2200 engine rpm with 16.9/14-30 rear tyres
Power Take-off	
Live single speed - 540 rpm	1,789 rpm
Shaft diameter/Number of splines	35mm / 6
Hydraulics	
Functions	Draft control, Position control. Response control, Constant pumping
Oil flow	litres/min 16.7
System pressure	Mpa 21.2
Lift capacity at lower link ends	kg 2,145
3-point linkage	Cat 1 & 2 interchangeable balls
Brakes	
Brake type	Oil-immersed, multi-disc
Actuation	Hydraulic
Parking brake	Hand lever operated
Differential lock	Mechanical
Tyres	
Front	7.50 - 16 (6PR) Pressed wheels
Rear	16.9 / 14 - 30 (6PR) Pressed wheels
Instrumentation	
Gauges	Tachometer, hourmeter, fuel level, battery condition & water temperature
Warning lights	Direction indicators, battery charge, headlight main beam, low engine oil pressure, brake lights & auxiliary socket

MF 375 Xtra

Weights and Dimensions*	
Gross weight	kg 2,295
Wheelbase	mm 2,170
Overall length - (links horizontal)	mm 3,670
Overall width (min)	mm 1,970
Overall height over exhaust	mm 2,485
Overall height over steering wheel	mm 1,730
Capacities	
Fuel tank	litres 108
Engine sump	litres 7.5
Cooling system	litres 15.2
Hydraulic system	litres 36
Steering box	litres 2.0
Oil bath air-cleaner	litres 0.7
Turning circle	
With brakes	mm 7,260
Without brakes	mm 8,095
Ground clearance	
Under gearbox	mm 501
Front axle	
Type	Heavy-duty box section, adjustable
Rear axle	
Type	Heavy-duty with epicyclic reduction
Track Adjustment	
Front	mm 1,271 - 1,881
Rear	mm 1,423 - 2,134
Steering	
Type	Hydrostatic

MF 375 Xtra

(with 7.50-16 front & 16.9/14-30 rear wheels)

Standard equipment

Frame and sun canopy, Flat top fenders, Stabiliser chains, Standard tool box, Top link end Cat I & II balls, Spring suspension seat, Weight frame without weights, Operator manual, Front-end weights

* Approximately ** Manufacturer's estimate

For even greater productivity a range of optional equipment is available. For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.