



CONTRACTOR LINE

MOBISCREEN MS 21 Z

TECHNICAL INFORMATION

■ TRACK-MOUNTED SCREENING PLANT



MOBISCREEN MS 21 Z
STANDARD VERSION

TECHNICAL SPECIFICATIONS MS 21 Z

Feeding unit		Bottom deck underflow discharge conveyor (fine fractions)	
Feed capacity up to approx. (t/h)	500	Width x length (mm)	1,050 x 7,910
Feed size max. (mm)	500	Discharge height approx. (mm)	3,500 - 4,000
Feed height (mm)	3,680	Bottom deck overflow discharge conveyor (medium fractions)	
Hopper capacity (m³)	11,5	Width x length (mm)	900 x 8,080
Belt conveyor (bottom deck)		Discharge height approx. (mm)	2,500 - 3,600
Width x length (mm)	1,400 x 5,520	Top deck overflow discharge conveyor (oversize fractions)	
Belt conveyor feeder		Width x length (mm)	1,600 x 5,840
Width x length (mm)	1,500 x 4,800	Discharge height approx. (mm)	2,800 - 3,800
Type (optional)	variable speed	Crawler chassis	
Screening unit		Type	D4
Type	double-deck vibration screen	Diesel-hydraulic drive	
Top deck width x length (mm)	1,830 x 6,100	Engine power (kW)	168
Bottom deck width x length (mm)	1,830 x 5,490	Transport	
		Transport height approx. (mm)	3,500
		Transport length approx. (mm)	16760,
		Transport width approx. (mm)	3,000
		Transport weight approx. (kg)	40,000 ¹⁾