



## 3412 HT / 3412 HT P

**3412 HT** - Compactor with vibratory smooth roller drum

**3412 HT P** - Compactor with vibratory padfoot drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Clear information display
- ▶ Hammtronic electronic machine management
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Hydrostatic steering
- ▶ Optimum ease of maintenance, long service intervals



# 3412 HT / 3412 HT P

3412 HT - Compactor with vibratory smooth roller drum  
3412 HT P - Compactor with vibratory padfoot drum



	3412 HT	3412 HT P
<b>Weights</b>		
Operating weight with ROPS	kg 11980	12080
Operating weight with cab	kg 12200	12300
Operating weight, max.	kg 15270	13830
Axle load, front/rear	kg 6705/5495	6805/5495
Load per tyre, rear	kg 2747,5	2747,5
Static linear load, front	kg/cm 31,3	
French classific., data/class	42,2/VM3	43,4/MPM3
<b>Machine dimensions</b>		
Max. working width	mm 2140	2140
Lateral overhang, left/right	mm 55/55	55/55
Ground clearance, left/right	mm 465/465	465/465
Ground clearance, centre	mm 375	375
Turning radius, inside	mm 3780	3690
Drum thickness, front	mm 30	20
Number of padfeet		140
Height of the padfeet	mm 100	100
Front area of padfeet	cm <sup>2</sup> 152	152
Size of tyres, rear	AW 23.1-26 12 PR	TR 23.1-26 12 PR
<b>Diesel engine</b>		
Manufacturer	DEUTZ	DEUTZ
Type	TCD 2012 L04 2V	TCD 2012 L04 2V
Number of cylinders	4	4
Power rat. ISO 14396, kW/PS/rpm	100,0/136,0/2300	100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm	100,0/134,0/2300	100,0/134,0/2300
Emissions standard EU/USA	III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L 290	290
<b>Drive</b>		
Hydrostatic drive, front/rear	Hydraulic motor/axle	Hydraulic motor/axle
Regulation, infinitely variable	Hammtronic/manual	Hammtronic/manual
Speed, infinitely variable	km/h 0 - 14,0	0 - 14,0
Climbing ability, vibration on/off	% 58/63	65/70

**Vibration system**  
Hydrostatic drive

<b>Vibration</b>			
Vibration frequency, front, I/II	Hz	30/40	30/40
Amplitude, front, I/II	mm	1,91/0,90	1,90/0,90
Centrifugal force, front, I/II	kN	256/215	256/215

<b>Steering</b>			
Steering, type		Articulated steering	Articulated steering
Steering, actuation		hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	°	35	35
Oscillation angle +/-	°	10	10

**Equipment**  
Spring-mounted driver seat, Double-sided access, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Excellent engine power with traction control, Automatic traction and slip control, Engine management, Speed pre-selection, Automatic frequency control with digital display, Swivelling steering and instrument console, Modern information and indicator display, Tilttable GRP bonnet

**Optional equipment**  
Spotlights, Exterior and interior mirrors, Radio, Heating with dust-free ventilation, Air conditioning, ROPS/FOPS, Sunroof, HCQ compression meter, Sound insulation, HCQ printer, HCQ GPS compression documentation, Tachograph

<b>Total length</b>	L	5870	5705
<b>Width</b>	B	2250	2250
<b>Total height</b>	H	2990	3010
<b>Wheel base</b>	A	3060	3015
<b>Roller drum width</b>	X	2140	2140
<b>Drum diameter</b>	D	1504	1684
<b>Width over tyres</b>	Y	2130	2130
<b>Diameter of tyres</b>	R	1565	1565
<b>Height loading, min.</b>	HI	2325	2325

