








### PRODUCT INDEX

	Series	Page
 Metric Polyurethane Tube Black/Blue/Red/White/Green/Yellow	<b>MPT</b>	<b>472</b>
 Imperial Nylon Tube Black/White/Blue/Red/Green/Yellow	<b>INT</b>	<b>473</b>
 Metric Nylon Tube Black/White/Blue/Red/Green/Yellow	<b>MNT</b>	<b>474</b>
 Air Brake Coils - Suzy Red / Yellow	<b>SUZY</b>	<b>475</b>
 Polyurethane Recoil Hose Assemblies	<b>RHC</b>	<b>475</b>

### Black Metric Polyurethane Tube - MPTN



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Black  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTN-004</b>	2.5	4	190	13
<b>MPTN-005</b>	3	5	160	11
<b>MPTN-006</b>	4	6	155	10.5
<b>MPTN-008</b>	5	8	150	10
<b>MPTN-010</b>	6.5	10	125	8.5
<b>MPTN-012</b>	8	12	120	8

### White Metric Polyurethane Tube - MPTW



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** White  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTW-004</b>	2.5	4	190	13
<b>MPTW-005</b>	3	5	160	11
<b>MPTW-006</b>	4	6	155	10.5
<b>MPTW-008</b>	5	8	150	10
<b>MPTW-010</b>	6.5	10	125	8.5
<b>MPTW-012</b>	8	12	120	8

4.  
2

### Blue Metric Polyurethane Tube - MPTB



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Blue  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTB-004</b>	2.5	4	190	13
<b>MPTB-005</b>	3	5	160	11
<b>MPTB-006</b>	4	6	155	10.5
<b>MPTB-008</b>	5	8	150	10
<b>MPTB-010</b>	6.5	10	125	8.5
<b>MPTB-012</b>	8	12	120	8

### Green Metric Polyurethane Tube - MPTG



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Green  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTG-004</b>	2.5	4	190	13
<b>MPTG-005</b>	3	5	160	11
<b>MPTG-006</b>	4	6	155	10.5
<b>MPTG-008</b>	5	8	150	10
<b>MPTG-010</b>	6.5	10	125	8.5
<b>MPTG-012</b>	8	12	120	8

### Red Metric Polyurethane Tube - MPTR



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Red  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTR-004</b>	2.5	4	190	13
<b>MPTR-005</b>	3	5	160	11
<b>MPTR-006</b>	4	6	155	10.5
<b>MPTR-008</b>	5	8	150	10
<b>MPTR-010</b>	6.5	10	125	8.5
<b>MPTR-012</b>	8	12	120	8

### Yellow Metric Polyurethane Tube - MPTY



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Yellow  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	Bore Size mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MPTY-004</b>	2.5	4	190	13
<b>MPTY-005</b>	3	5	160	11
<b>MPTY-006</b>	4	6	155	10.5
<b>MPTY-008</b>	5	8	150	10
<b>MPTY-010</b>	6.5	10	125	8.5
<b>MPTY-012</b>	8	12	120	8

### Black Imperial Nylon Tube - BS5409 - INTN

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Black  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTN-02</b>	02	0.075	1/8	300	20
<b>INTN-03</b>	03	0.117	3/16	300	20
<b>INTN-04</b>	04	0.170	1/4	300	20
<b>INTN-05</b>	05	0.212	5/16	250	17
<b>INTN-06</b>	06	0.250	3/8	250	17
<b>INTN-08</b>	08	0.375	1/2	250	17

### Red Imperial Nylon Tube - BS5409 - INTR

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Red  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTR-04</b>	04	0.170	1/4	300	20
<b>INTR-05</b>	05	0.212	5/16	250	17
<b>INTR-06</b>	06	0.250	3/8	250	17
<b>INTR-08</b>	08	0.375	1/2	250	17

### White Imperial Nylon Tube - BS5409 - INTW

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** White  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTW-02</b>	02	0.075	1/8	300	20
<b>INTW-03</b>	03	0.117	3/16	300	20
<b>INTW-04</b>	04	0.170	1/4	300	20
<b>INTW-05</b>	05	0.212	5/16	250	17
<b>INTW-06</b>	06	0.250	3/8	250	17
<b>INTW-08</b>	08	0.375	1/2	250	17
<b>INTW-10</b>	10	0.500	5/8	200	14
<b>INTW-12</b>	12	0.594	3/4	200	14
<b>INTW-16</b>	16	0.813	1	180	12

### Green Imperial Nylon Tube - BS5409 - INTG

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Green  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTG-04</b>	04	0.170	1/4	300	20
<b>INTG-05</b>	05	0.212	5/16	250	17
<b>INTG-06</b>	06	0.250	3/8	250	17
<b>INTG-08</b>	08	0.375	1/2	250	17

### Blue Imperial Nylon Tube - BS5409 - INTB

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Blue  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTB-04</b>	04	0.170	1/4	300	20
<b>INTB-05</b>	05	0.212	5/16	250	17
<b>INTB-06</b>	06	0.250	3/8	250	17
<b>INTB-08</b>	08	0.375	1/2	250	17

### Yellow Imperial Nylon Tube - BS6509 - INTY

**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Yellow  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C



Part Number	Size	I.D. ins	O.D. ins	Working Pressure PSI	Working Pressure Bar
<b>INTY-04</b>	04	0.170	1/4	300	20
<b>INTY-05</b>	05	0.212	5/16	250	17
<b>INTY-06</b>	06	0.250	3/8	250	17
<b>INTY-08</b>	08	0.375	1/2	250	17

### White Metric Nylon Tube

- BS 5409 - MNTW



**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** White  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTW-004</b>	2.5	4	580	40
<b>MNTW-005</b>	3	5	580	40
<b>MNTW-006</b>	4	6	580	40
<b>MNTW-008</b>	6	8	580	40
<b>MNTW-010</b>	8	10	580	40
<b>MNTW-012</b>	9	12	580	40

### Red Metric Nylon Tube

- BS 5409 - MNTR



**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Red  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTR-004</b>	2.5	4	580	40
<b>MNTR-006</b>	4	6	580	40
<b>MNTR-008</b>	6	8	580	40
<b>MNTR-010</b>	8	10	580	40
<b>MNTR-012</b>	9	12	580	40

4.  
2

### Black Metric Nylon Tube

- BS 5409 - MNTN



**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Black  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTN-004</b>	2.5	4	580	40
<b>MNTN-005</b>	3	5	580	40
<b>MNTN-006</b>	4	6	580	40
<b>MNTN-008</b>	6	8	580	40
<b>MNTN-010</b>	8	10	580	40
<b>MNTN-012</b>	9	12	580	40

### Green Metric Nylon Tube

- BS 5409 - MNTG



**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Green  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTG-004</b>	2.5	4	580	40
<b>MNTG-006</b>	4	6	580	40
<b>MNTG-008</b>	6	8	580	40
<b>MNTG-010</b>	8	10	580	40
<b>MNTG-012</b>	9	12	580	40

### Blue Metric Nylon Tube

- BS 5409 - MNTB



**Tube:** Nylon Type 12  
**Reinforcement:** Unreinforced  
**Cover:** Blue  
**Coil Lengths:** 30 metres  
**Temperature Range:** -20°C to +100°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTB-004</b>	2.5	4	580	40
<b>MNTB-006</b>	4	6	580	40
<b>MNTB-008</b>	6	8	580	40
<b>MNTB-010</b>	8	10	580	40
<b>MNTB-012</b>	9	12	580	40

### Yellow Metric Nylon Tube

- BS 5409 - MNTY



**Tube:** Polyurethane  
**Reinforcement:** Unreinforced  
**Cover:** Yellow  
**Coil Lengths:** 25 metres  
**Temperature Range:** -20°C to +75°C

Part Number	I.D. mm	O.D. mm	Working Pressure	
			PSI	Bar
<b>MNTY-004</b>	2.5	4	580	40
<b>MNTY-006</b>	4	6	580	40
<b>MNTY-008</b>	6	8	580	40
<b>MNTY-010</b>	8	10	580	40
<b>MNTY-012</b>	9	12	580	40

### Air Brake Coils - Suzy Red



Part Number	I.D. mm	O.D. (mm)
<b>SUZY RED</b>	9	12

### Air Brake Coils - Suzy Yellow



Part Number	I.D. mm	O.D. (mm)
<b>SUZY YELLOW</b>	9	12

### Polyurethane Recoil Hose Assemblies - RHC

These assemblies have low resistance to extension forces so worker fatigue is substantially reduced. Applications cover most pneumatic and other uses that have requirements from -40°F to +180°F (-40°C to +82°C) and a nominal working pressure of 100 psi @ +75°F (24°C).

#### Features

- Kink Resistance
- Wear Resistant
- Light weight and mobile
- Straight BSPT swivel male ends
- Stretches full length
- Low working fatigue
- Excellent oxidation, chemical, hydrolysis and ozone resistance



4.  
2

Part Number	ID (mm)	O.D. (mm)	Working length mtrs	Coil ID (mm)	Colour	Swivel BSPT male ends
<b>RHC-08-2MY</b>	5	8	2.5	25	Yellow	1/4
<b>RHC-08-4MY</b>	5	8	4	25	Yellow	1/4
<b>RHC-08-7MY</b>	5	8	7.5	25	Yellow	1/4
<b>RHC-10-2MY</b>	6.5	10	2.5	30	Yellow	1/4
<b>RHC-10-5MY</b>	6.5	10	5	30	Yellow	1/4
<b>RHC-10-7MY</b>	6.5	10	7.5	30	Yellow	1/4
<b>RHC-12-2MY</b>	8	12	2.5	40	Yellow	3/8
<b>RHC-12-5MY</b>	8	12	5	40	Yellow	3/8
<b>RHC-12-7MY</b>	8	12	7.5	40	Yellow	3/8
<b>RHC-16-2MY</b>	11	16	2.5	70	Yellow	1/2
<b>RHC-16-5MY</b>	11	16	5	70	Yellow	1/2
<b>RHC-16-7MY</b>	11	16	7.5	70	Yellow	1/2
<b>RHC-08-2MB</b>	5	8	2.5	25	Blue	1/4
<b>RHC-08-4MB</b>	5	8	4	25	Blue	1/4
<b>RHC-08-7MB</b>	5	8	7.5	25	Blue	1/4
<b>RHC-10-2MB</b>	6.5	10	2.5	30	Blue	1/4
<b>RHC-10-5MB</b>	6.5	10	5	30	Blue	1/4
<b>RHC-10-7MB</b>	6.5	10	7.5	30	Blue	1/4
<b>RHC-12-2MB</b>	8	12	2.5	40	Blue	3/8
<b>RHC-12-5MB</b>	8	12	5	40	Blue	3/8
<b>RHC-12-7MB</b>	8	12	7.5	40	Blue	3/8
<b>RHC-16-2MB</b>	11	16	2.5	70	Blue	1/2
<b>RHC-16-5MB</b>	11	16	5	70	Blue	1/2
<b>RHC-16-7MB</b>	11	16	7.5	70	Blue	1/2
<b>RHC-08-2MR</b>	5	8	2.5	25	Red	1/4
<b>RHC-08-4MR</b>	5	8	4	25	Red	1/4
<b>RHC-08-7MR</b>	5	8	7.5	25	Red	1/4
<b>RHC-10-2MR</b>	6.5	10	2.5	30	Red	1/4
<b>RHC-10-5MR</b>	6.5	10	5	30	Red	1/4
<b>RHC-10-7MR</b>	6.5	10	7.5	30	Red	1/4
<b>RHC-12-2MR</b>	8	12	2.5	40	Red	3/8
<b>RHC-12-5MR</b>	8	12	5	40	Red	3/8
<b>RHC-12-7MR</b>	8	12	7.5	40	Red	3/8
<b>RHC-16-2MR</b>	11	16	2.5	70	Red	1/2
<b>RHC-16-5MR</b>	11	16	5	70	Red	1/2
<b>RHC-16-7MR</b>	11	16	7.5	70	Red	1/2